

INSTALLATION MANUAL

SNAP RING / BRACKET MOUNT

Level of Difficulty

Easy

Installation difficulty levels are based on time and effort involved and may vary depending on the installer level of expertise, condition of the vehicle and proper tools and equipment.

Weight Carrying Capacity

Refer to capacity listed on the product label

Parts List

Item	Qty	Description
1	1	Jack
2	2	Mounting bracket
3	4	Hex bolt
4	4	Nylock nut

*Hardware specifications will vary depending on product

Tools Required

Socket set	--
------------	----

NOTICE

Visit www.curtmfg.com for a full-color copy of this instruction manual, as well as helpful videos, guides and much more!

Before you begin installation, read all instructions thoroughly.

Proper tools will improve the quality of installation and reduce the time required.

Periodic inspection of your product should be performed to ensure all hardware and / or components remain secure.

Product Registration and Warranty

CURT stands behind our products with industry-leading warranties. To get copies of the product warranties, register your purchase or provide feedback, visit: curtmfg.com/registration

⚠ WARNING

Do not exceed the rated capacity or severe product damage, serious personal injury or death may occur. Keep people and pets at a safe distance during installation and operation of the trailer jack.

This installation may create a condition where severe product damage, serious personal injury or death may occur if stated precautions are not followed.

The trailer **MUST** be supported per the manufacturer's recommendations before working underneath. Failure to do so may result in death, serious personal injury or severe product or property damage.

Product Photo



Actual product appearance will depend on part # purchased

⚠ CAUTION

Moving parts can pinch, crush or cut. Keep clear and use caution.

Fully lower jack before rotating jack to stored position.

Before manually moving trailer, ensure jack is in the lowest position.

Step 1

Place the jack against the tongue and position the mounting straps on the opposite side of the tongue.

Align the holes in the mounting bracket with the holes in the mounting straps.

Insert the four hex bolts through the mounting bracket and mounting straps. The upper bolts should rest on the top of the tongue and the lower bolts should be less than 1/16" from the bottom of the tongue.

Secure with locknuts and snug the hardware to the mounting brackets.

